

TK-0351 BURNISH BLOCK SEALER GLOSS

Color	CLEAR	
Packaging	1 GALLON CAN, 5 GALLON PAIL, 55 GALLON DRUM	
Vehicle Type	METHACRYLATED ACRYLIC	
Solvent Type	AROMATIC/ESTER BLEND	
Gloss at 60° angle	90+	
% Solids by Weight	27 – 28%	
Viscosity at 77° F	22 – 24 SECONDS ZAHN #2	
Desired Dry Film	1.0 – 1.25 MILS	
Recommended Coverage Rate*	300 – 350 FT ² /GALLON	
Average Dry Time at 70° F	Tack Free	5 – 10 MINUTES
	Recoat	10 MINUTES
	Full Cure	4 – 8 HOURS
Catalyst	N/A – SINGLE COMPONENT	
Thinner	TOLUENE	
Mix Ratio	N/A	
Pot Life	N/A	
Recommended Primer	Steel	N/A
	Galvanized	N/A
	Concrete	N/A
Flash Point	40°F	
V.O.C.	682 GRAMS/LITER (5.69 LB/GAL)	
A.I.M. Category V.O.C. Limit	EXEMPT – IN PLANT USE ONLY	

*Coverage: Theoretical coverage rates are a laboratory calculation based on the solids content and the desired dry film thickness. It does not take into consideration substrate porosity, application procedures, weather conditions, over-spray and wind loss.

9/24/02

It is always advisable to apply a test panel or mock up prior to the project start up. This will help to determine proper coverage, appearance and equipment requirements.

General Description:

TK-0351 IS A NON-YELLOWING METHACRYLATED ACRYLIC DESIGNED ESPECIALLY FOR IN-PLANT APPLICATION TO BURNISHED BLOCK. TK-0351 WILL PROVIDE A GLOSS FINISH AND "WET LOOK" THAT ENHANCES THE APPEARANCE OF THE BLOCK. ITS BLEND OF FAST EVAPORATION SOLVENTS ALLOW FOR A FAST DRY TO MEET THE DEMAND OF A PRODUCTION ENVIRONMENT.

Resistance to:

Abrasion	EXCELLENT
Acid	EXCELLENT
Alkali	EXCELLENT
Humidity	EXCELLENT
Petroleum Products	POOR
Salt Spray	EXCELLENT
Weather	EXCELLENT

Mixing Detail:

PRODUCT IS SUPPLIED READY TO USE. THERE ARE NO SPECIAL MIXING INSTRUCTIONS.

Surface Preparation:

BLOCK SHOULD BE CLEAN AND DRY. ANY DUST OR WATER FROM THE GRINDING OPERATION SHOULD BE AIR-KNIFED CLEAN.

Application Procedure:

APPLY BY AIRLESS SPRAY. AS A STARTING RECOMMENDATION USE A .015 – .017 TIP AT A PRESSURE OF 1950 LBS. THE END USER SHOULD OPTIMIZE THEIR SYSTEM TO BEST SUIT THEIR NEEDS.

Clean Up:

CLEAN TOOLS AND SPILLS WITH XYLENE.

Safety Information:

THIS PRODUCT CONTAINS CHEMICALS WHICH HAVE ASSOCIATED HEALTH AND FIRE HAZARDS. AVOID BREATHING VAPORS AND MINIMIZE CONTACT. ALWAYS WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. KEEP AWAY FROM SPARKS AND OPEN FLAMES, OR ANY SOURCE OF IGNITION. DISPOSE OF EMPTY CONTAINERS IN ACCORDANCE TO ALL APPLICABLE REGULATIONS.

CONSULT THIS PRODUCT'S MSDS FOR FURTHER INFORMATION.

HMIS:

HEALTH	2*
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	I

Conditions Of Sale/Limited Warranty:

TK Products, division of The Sierra Corporation, warrants that this product conforms to the label descriptions, is free from manufacturing defects and is fit for the ordinary purposes for which such goods are used. Inasmuch as the use of this product by others and other factors affecting product performance are beyond TK Product's control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT OR, AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF THIS PRODUCT TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN THE CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of this product unless specifically authorized by TK Products in writing.