



Division of Sierra Corporation  
ISO 9001:2008 Certified

# TK-AIRMAX 2200 ALL WEATHER FLASHING TAPE

## Technical Data

### 1. PRODUCT NAME

TK-AIRMAX 2200 ALL WEATHER FLASHING TAPE

### 2. MANUFACTURER

TK PRODUCTS  
DIVISION OF SIERRA CORPORATION  
11400 West 47th Street  
Minnetonka, MN 55343  
952-938-7223  
952-938-8084 (FAX)  
e-mail: [tksales@tkproduct.com](mailto:tksales@tkproduct.com)  
Website: <http://www.tkproduct.com>

### 3. PRODUCT DESCRIPTION

TK-AIRMAX 2200 ALL WEATHER FLASHING TAPE is a low permeability, self-adhering air, moisture and vapor barrier. Durable and resistant to tears and puncturing, TK-AIRMAX 2200 ALL WEATHER FLASHING TAPE is ideal for both commercial and residential applications.

TK-AIRMAX 2200 ALL WEATHER FLASHING TAPE adheres well to a wide range of construction materials and applies easily at temperatures as low as 5°F (-13°C).

TK-AIRMAX 2200 ALL WEATHER FLASHING TAPE cuts and installs easily and successfully conforms to irregular surfaces. Convenient roll size options offer application flexibility, efficiency, and cost savings.

Available in standard and custom roll sizes, TK-AIRMAX 2200 ALL WEATHER FLASHING TAPE is a versatile, high performance air barrier for a broad range of applications.

#### Features and Benefits:

- Low permeability
- Self-adhering air, moisture and vapor barrier
- Conforms well to irregular surfaces
- Cuts and applies easily
- Applies easily at temperatures as low as 5°F (-13°C)
- Ideal for interior as well as exterior applications

- Bonds to a wide variety of materials including polyethylene, HouseWrap, metal, insulation, foam, fiberglass, fabrics, glass and plastics as well as other natural and synthetic materials.
- No special tools required for application

### 4. TECHNICAL DATA

Specification	Typical Value	Test Method
Base Material	UV Stable Proprietary Film	
Adhesive Tape	Acrylic	
Peel Adhesion - Anodized Aluminum	70 oz/in	PSTC-101
Peel Adhesion - Polyethylene	60 oz/in	PSTC-101
Peel Adhesion - Oriented Strand Board	60 oz/in	PSTC-101
Peel Adhesion - HouseWrap	50 oz/in	PSTC-101
Nail Sealability	Pass	ASTM E 331
Temperature Range	5°F to 176°F	
Flame Spread/Smoke Developed	5/25	ASTM E 84
Water Vapor Permeability	0.1866 Perms	ASTM E 96

### 6. AVAILABILITY/CONFIGURATIONS

- Standard Widths: 3", 6", 12", 18", 24", 38 1/2"
- Standard Length: 75 Feet

Additional roll widths and lengths available - contact TK Products for information.

### 7. LIMITED WARRANTY

TK Products, a division of The Sierra Corporation, warrants that its products conform to their label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of its products by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. SHOULD ANY OF ITS PRODUCTS FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCTS OR, AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF THE PRODUCTS OF TK PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing. See also TK PRODUCTS DISCLAIMER section below.

### 8. TECHNICAL SERVICES

The TK office offers assistance with specifications, performance test data and field services.

### 9. FILING SYSTEMS

Information Handling Services  
PO BOX 1213  
Englewood, CO 80150  
Information Marketing Services  
13271 Northend  
Oak Park, MI 48237

### TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field test by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also LIMITED WARRANTY (Section 7) above.

**FOR INDUSTRIAL USE ONLY**