

TK-5761 08

TRI-SILOXANE IN TOLUENE

8% ACTIVE

Color	CLEAR	
Packaging	METAL 5 GALLON PAILS, 55 GALLON LINED DRUMS	
Vehicle Type	ORGANO SILOXANE	
Solvent Type	TOLUENE	
Gloss at 60° angle	DOES NOT FORM A FILM	
% Solids by Weight	8%	
Viscosity at 77° F	WATER-LIKE	
Desired Dry Film	N/A	
Recommended Coverage Rate*	75 – 125 FT ² /GALLON	
Average Dry Time at 70° F	Tack Free	10 – 30 MINUTES
	Recoat	2 – 4 HOURS
	Full Cure	OVERNIGHT
Catalyst	N/A	
Thinner	DO NOT THIN	
Mix Ratio	N/A	
Pot Life	N/A	
Recommended Primer	Steel	N/A
	Galvanized	N/A
	Concrete	N/A
Flash Point	40°F	
V.O.C.	810 GRAMS PER LITER	
A.I.M. Category V.O.C. Limit	NOT REGULATED WHEN APPLIED IN PLANT	

*Coverage: Theoretical coverage rates are a laboratory calculation based on the solids content and the desired dry film thickness. It does not take into consideration substrate porosity, application procedures, weather conditions, over-spray and wind loss.

2/23/06

It is always advisable to apply a test panel or mock up prior to the project start up. This will help to determine proper coverage, appearance and equipment requirements.

General Description:

TK-5671 08 IS A FAST-DRY SILOXANE WATER PROOFING TREATMENT FOR STANDARD WEIGHT TO DENSE BURNISHED BLOCK. IT PENETRATES UP TO 1/4 INCH INTO THE SUBSTRATE AND CHEMICALLY REACTS WITH THE CONCRETE TO FORM A HYDROPHOBIC SURFACE WHICH WILL BEAD WATER UPON CONTACT YET CAN BE RE-SEALED WITH A DECORATIVE SEALER.

Resistance to:

Abrasion	EXCELLENT
Acid	EXCELLENT
Alkali	EXCELLENT
Humidity	EXCELLENT
Petroleum Products	EXCELLENT
Salt Spray	EXCELLENT
Weather	EXCELLENT

Mixing Detail:

PRODUCT IS SUPPLIED READY TO USE. NO MIXING IS NECESSARY.

Surface Preparation:

SURFACE MUST BE CLEAN AND DRY. GRINDING DUSTS SHOULD BE REMOVED BY BRUSHING OR AIR BRUSH. MUST BE APPLIED DIRECTLY TO BLOCK BEFORE ANY MEMBRANE FORMING SEALER. WET GRINDING PROCESSES MUST ALLOW BLOCK TO THOROUGHLY DRY BEFORE APPLICATION.

Application Procedure:

APPLY IN LINE WITH CONVENTIONAL OR AIRLESS SPRAY FLOODING MATERIAL ON TO THE SUBSTRATE TO THE POINT OF SATURATION. TYPICAL APPLICATION RATES ARE 75-125 FT²/ GALLON.

Clean Up:

CLEAN EQUIPMENT AND SPILLS WITH XYLENE.

Safety Information:

CONTAINS ORGANIC SOLVENTS WHICH HAVE HEALTH AND FIRE HAZARDS. AVOID BREATHING VAPORS AND OVERSPRAY MISTS. ALWAYS WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. GROUND ALL CONTAINERS AND SPRAY EQUIPMENT. DISPOSE OF EMPTY CONTAINER IN ACCORDANCE TO ALL APPLICABLE REGULATIONS.

SEE THIS PRODUCTS MSDS FOR FURTHER INFORMATION.

FIRST AID:

INHALATION: REMOVE FROM EXPOSURE TO FRESH AIR, TREAT SYMPTOMATICALLY, CALL A PHYSICIAN.

EYE CONTACT: IMMEDIATELY IRRIGATE WITH WATER FOR AT LEAST 15 MINUTES; GET MEDICAL ATTENTION.

SKIN CONTACT: WIPE OFF MATERIAL AND WASH THOROUGHLY WITH SOAP AND WATER.

INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING GET MEDICAL ATTENTION.

HMIS:

HEALTH	2*
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	I

Conditions Of Sale/Limited Warranty:

TK Products, division of The Sierra Corporation, warrants that this product conforms to the label descriptions, is free from manufacturing defects and is fit for the ordinary purposes for which such goods are used. Inasmuch as the use of this product by others and other factors affecting product performance are beyond TK Product's control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT OR, AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF THIS PRODUCT TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN THE CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of this product unless specifically authorized by TK Products in writing.