

1. PRODUCT NAME

TK-KURE & SEAL WB CURING AND SEALING COMPOUND

2. MANUFACTURER

TK PRODUCTS, DIVISION OF SIERRA CORPORATION
11400 West 47th Street
Minnetonka, MN 55343
952-938-7223
952-938-8084 (FAX)
e-mail: tkproduct@aol.com
Website: <http://www.tkproduct.com>

3.. PRODUCT DESCRIPTION

TK-KURE & SEAL WB is a 100% acrylic polymer water based membrane forming, curing, sealing and hardening compound for use on new or existing concrete. TK-KURE & SEAL WB is VOC Compliant.

TK-KURE & SEAL WB is formulated to cure, seal, protect and dustproof concrete as well as to seal many types of porous tile and resilient floor and wall coverings.

TK-KURE & SEAL WB is designed for both interior and exterior application; however, it is particularly recommended for indoor work in public buildings and housing (hospital, restaurants and private residences where solvent systems are difficult to use). The cloudy white solution dries clear and provides a dust free surface.

TK-KURE & SEAL WB provides maximum hardness to the concrete and traffic abrasion resistance. Construction debris does not adhere to the surface, cleanup is easier, less expensive. These products are compatible with most tile and carpet adhesives.

Uses:

Institutional, industrial, commercial and residential construction of floors, walls, columns. i.e.: schools, apartment complexes, hospitals, office buildings.

4. TECHNICAL DATA

Composition and Material:

TK-KURE & SEAL WB is formulated of fine quality, extremely hard but pliable, acrylic polymers in an aqueous system. It is carefully blended and quality controlled. It contains no oils saponifiable resins, or waxes.

Physical and Chemical Properties:

Non-flammable, non-toxic, no additional ventilation.

Dry Time: 2-4 hour (touch)
4-12 hours (traffic)

These dry times are dependent on normal drying conditions. Cool temperatures, high humidity will slow the drying time.

-Moisture Efficiency: .54 kg/m² at 200 sq. ft. per gallon.

-ASTM C-309 - maximum allowed .55 kg/m².

Applicable Standards:

Recommended for use on Class 1, 2, 3 and 4 concrete floors as noted in ACI Standard 302-77. TK-KURE & SEAL WB is designed to meet or exceed the following requirements.

-ASTM C-309, Type 1, Class A & B, and Type 1D when a red dye is added.

-AASHTO M-148 Type 1.

-Meets state and federal solvent emission standards (V.O.C.).

-USDA authorization for use.

-Compatible with carpet and resilient tile adhesives.

-A.I.M. Category: Concrete Curing Compound, maximum VOC 350g/l.

-A.I.M. Definition: A coating formulated and recommended for application to freshly placed concrete to retard the evaporation of water.

5. APPLICATION PROCEDURES AND INSTRUCTIONS

TK-KURE & SEAL WB is ready to use, do not dilute. Stir before using. **New Concrete:** Apply immediately after surface water has dissipated, and concrete can withstand weight. Spray application is best, however, other application methods can be used, i.e. lamb's wool applicator, or medium nap roller also can be used.

Existing Concrete: Sweep or vacuum all loose soil and dust. Remove oil, grease stains and old wax or polish. Tri-sodium phosphate or TK-101 Chemical Cleaner (with very hot water) can be used; rinse thoroughly and allow to dry. TK-KURE & SEAL WB can be applied by lamb's wool applicator, or medium nap roller. On large areas a sprayer can be used.

A second coat may be applied after the first coat is dry. This will provide greater protection and enhancement of the surface.

Curing	Coverage:	sq. ft./ gallon
broomed		200-250
troweled		200-300
Second coat		200-300

Limitations:

Avoid a buildup which can cause slippery conditions or a lifting action between coats. Protect from freezing. Do not apply if concrete surface and ambient temperatures are below 45° F.

Prolonged exposure to moisture or water may result in a temporary whitening of the film, which will clear upon drying.

Do not expose to water or rain until the film has dried hard.

Cleanup of Tools and Equipment:

Use soap and water before material dries. If dried, use MEK (methyl ethyl ketone).

Precautions:

Contains minute amount of ammonia. Excessive and prolonged inhalation may result in headaches, nausea, and eye or lung irritation.

First Aid:

Inhalation: Remove from exposure to fresh air, treat symptomatically, call a physician. *Eye Contact:* Immediately irrigate with water for at least 15 minutes; get medical attention. *Skin Contact:* Wipe off material and wash thoroughly with soap and water. *Ingestion:* Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Get medical attention.

6. AVAILABILITY

TK-KURE & SEAL WB is available through TK Distributors. Contact TK PRODUCTS for the nearest distributor. Packaged in: 55 gallon drums, 5 gallon pails, and one gallon cans.

Maintenance:

Stains should be removed as soon as possible. TK-KURE & SEAL WB can be applied to wear areas and where spills have removed the sealer.

7. LIMITED WARRANTY

TK Products, a division of The Sierra Corporation, warrants that its products conform to their label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of its products by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. SHOULD ANY OF ITS PRODUCTS FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCTS OR, AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF THE PRODUCTS OF TK PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR

INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing. See also TK PRODUCTS DISCLAIMER section below.

8. TECHNICAL SERVICES

The TK office offers assistance with specifications, performance test data, field services.

9. FILING SYSTEMS

Information Handling Services:
PO BOX 1213
Englewood, CO 80150
Information Marketing Services:
13271 Northend
Oak Park, MI 48237

TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also LIMITED WARRANTY (Section 7) above.

FOR INDUSTRIAL USE ONLY

2/00